



148.00 EUR
 incl. 19% VAT, plus [shipping](#)

- VIA C7 NanoBGA CPU
- 1.5 Ghz !
- DDR-II !
- 12W

This board is based on the latest VIA C7 architecture.

| 7F2WE-1G5-OC Specifications | |
|-----------------------------|---------------------------------------|
| Processor | VIA C7 1.5 GHz processor |
| Chipset | VIA CN700 north bridge |
| | VIA VT8237R south bridge |
| System Memory | 1 DDR2 400/533 DIMM |
| | Up to 1GB memory size |
| VGA | Integrated VIA UniChrome AGP graphics |
| Expansion Slots | 1 PCI |
| Onboard IDE | 4 Ultra DMA 133 |
| Onboard Serial ATA | 2 SATA connectors |
| Onboard Floppy | 1 Floppy Port |
| Onboard USB | 8 USB 2.0 |
| Onboard LAN | VIA 6103 10/100 |
| Onboard Audio | ALC655 6 channel AC'97 codec |
| Onboard TV Out | VIA VT1622A TV encoder |
| Onboard 1394 | IEEE 1394 |

| | |
|---|---|
| Back Panel I/O | <p>1 1394</p> <p>1 RCA video</p> <p>1 VGA port</p> <p>2 USB 2.0</p> <p>1 LAN port</p> <p>2 IEEE 1394 ports</p> <p>1 serial ports</p> <p>1 PS2 mouse port</p> <p>1 PS2 keyboard port</p> <p>3 audio jacks: line-out, line-in, and mic-in</p> |
| Onboard I/O Connectors | <p>3 USB 2.0 connectors for 6 USB ports</p> <p>1 parallel port</p> <p>1 VGA port</p> <p>2 serial ports</p> <p>1 PS2 keyboard connector</p> <p>1 PS2 mouse connector</p> <p>1 floppy port</p> <p>Line-in/out/MIC audio ports</p> |
| BIOS | <p>Award BIOS LPC 4Mbit Flash memory</p> |
| System Monitoring & Management | <p>CPU temperature</p> <p>Modem ring wake up</p> <p>RTC Alarm</p> <p>Keyboard power on</p> <p>System temperature</p> <p>System voltage</p> <p>Fan speed</p> |
| Operating Humidity | <p>0% - 95% (relative humidity; non-condensing)</p> |
| Form Factor | <p>Mini-ITX (17cm x 17cm)</p> |
| Includes | <p>ATA 133 flat cable (40 wire, 80 conductor, 3 connectors)</p> <p>CD</p> <p>SATA Cable</p> <p>Floppy Cable</p> |