



39.95 EUR incl. 19% VAT, plus shipping

Support: <u>Heatsink-Height</u>

The Intel® Desktop Board D201GLY2 is an innovative solution for the sub-value market segment. With an Intel® Celeron® processor and graphics integrated on the board, this board enables easy system integration and helps you to achieve a lower system cost. This board has 10/100 LAN, support up to six Hi-Speed USB 2.0 ports and 2 SATA (1.5 GB/s), providing both connectivity and ease of use for your computing needs such as email and Internet access, instant messaging and Voice Over IP (VoIP).

The Intel Desktop Board D201GLY2 is built in smaller uATX-Compatible form factor providing lower power consumption and passive thermal solution.

| Form Factor | uATX (6.75 inches by 6.75 inches [171.45 millimeters by 171.45 |
|------------------------|--|
| | millimeters]) (ITX compatible) |
| Processor | Integrated Intel® Celeron® 220 processor (1.2 Ghz) with a 533 |
| | MHz system bus |
| Memory | One 240-pin DDR2 SDRAM Dual Inline Memory Module (DIMM) |
| | sockets |
| | Support for DDR2 677/533/400 MHz DIMMs |
| | Support for up to 1 GB of system memory |
| Chipset | SiS* SiS662 Northbridge |
| | SiS* SiS964L Southbridge |
| Audio | ADI* AD1888 audio codec |
| Video | Integrated SiS Mirage* 1 graphic engine |
| I/O Control | Winbond* W83627DHG-B based Legacy I/O controller for |
| | hardware management, serial, parallel, and PS/2* ports |
| LAN Support | 10/100 Mbits/sec LAN subsystem using the Broadcom* LAN |
| | adapter device |
| Peripheral Interfaces | Six USB 2.0 ports |
| | One parallel ATA IDE interface with UDMA 33, ATA-66/100/133 |
| | support |
| | Two SATA ports |
| | One serial port |
| | One parallel port |
| | PS/2* keyboard and mouse ports |
| Expansion Capabilities | One PCI Conventional* bus connector |

Note: The CPU heatsink has a height of 45mm. Thats why it does not fit into every enclosure. Compatible with:

Intel D201GLY2 (with integrated Celeron 1.2Ghz CPU) [FANLESS]

[http://www.cartft.com/catalog/il/844]



- Voom
- Voom-2
- M300(-LCD)
- Travla C137

Not compatible with:

- M200(-LCD)
- Morex enclosures (without PCI slot)

PicoPSU & M3-ATX: You can only directly stick in the standard picoPSU-120 power supply. Other picoPSU models and M3-ATX can only be connected with an additional ATX extension cable.

For Operating you need a P4 adapter or a PSU with P4 connector